

Magnet Wire - Component

COMPANY

Tongling Jingda Special Magnet Wire Co Ltd

No.988 Huangshan Avenue
Tongling Economic &
Technological Development Zone
Tongling, Anhui 244000 China

E248026

Material Designation	Mark Dsg	Base Coat	Top Coat	ANSI Type	Temp Class
El/AIWA-x\$, Q(ZY/XY)-A-x\$	El/AIWA-x, Q(ZY/XY)-A-x	Polyester-imide	Polyamide-imide	MW 35A	220[#]
JXMW24A-x\$, QZ/N-x 155-A\$, xPEW N/155A\$, JXMW24A(GRx)\$, QZ/N 155-A(GRx)\$	JXMW24A-x, QZ/N-x 155-A, xPEW N/155A, JXMW24A(GRx), QZ/N 155-A(GRx)	Polyester	Polyamide	MW 24A	155[#]
JXMW24C-x\$, QZ/N-x 155\$, xPEW N/155\$, JXMW24C(GRx)\$, QZ/N 155(GRx)\$	JXMW24C-x, QZ/N-x 155, xPEW N/155, JXMW24C(GRx), QZ/N 155(GRx)	Polyester	Polyamide	MW 24C	155[#]
JXMW28A-x\$, QA/N-x 130-A\$, xUEW N/130A\$, JXMW28A(GRx)\$, QA/N 130A(GRx)\$	JXMW28A-x, QA/N-x 130-A, xUEW N/130A, JXMW28A(GRx), QA/N 130A(GRx)	Polyurethane	Polyamide	MW 28A	130[#]
JXMW28C-x\$, QA/N-x 130\$, xUEW N/130\$, JXMW28C(GRx)\$, QA/N 130(GRx)\$	JXMW28C-x, QA/N-x 130, xUEW N/130, JXMW28C(GRx), QA/N 130(GRx)	Polyurethane	Polyamide	MW 28C	130[#]
JXMW30C-x\$, QZ-x/180\$, xPEW/180\$, JXMW30C(GRx)\$, QZ/180(GRx)\$	JXMW30C-x, QZ-x/180, xPEW/180, JXMW30C(GRx), QZ/180(GRx)	Polyester	-	MW 30C	180
JXMW35A-x\$, Q(ZY/XY)-x/220(L)\$, xEIAIW/220A\$, JXMW35A(GRx)\$, Q(ZY/XY)BP-x/220(L)\$	JXMW35A-x\$, Q(ZY/XY)-x/220(L)\$, xEIAIW/220A\$, JXMW35A(GRx)\$, Q(ZY/XY)BP-x/220(L)\$	Polyester-imide	Polyamide-imide	MW 35A	220
JXMW35A-x\$, Q(ZY/XY)-x/220(L)\$, xPEAIW/220A\$, JXMW35A(GRx)\$, Q(ZY/XY)BP-x/220(L)\$	JXMW35A-x\$, Q(ZY/XY)-x/220(L)\$, xPEAIW/220A\$, JXMW35A(GRx)\$, Q(ZY/XY)BP-x/220(L)\$	Polyester	Polyamide-imide	MW 35A	220

JXMW35C-x\$, Q(ZY/XY)-x/200\$, xEIAIW/200\$, JXMW35C(GRx)\$	JXMW35C-x, Q(ZY/XY)-x/200, xEIAIW/200, JXMW35C(GRx)	Polyester-imide	Polyamide-imide	MW 35C	200[#]
JXMW35C-x\$, Q(ZY/XY)-x/200\$, xPEAIW/200\$, JXMW35C(GRx)\$	JXMW35C-x, Q(ZY/XY)-x/200, xPEAIW/200, JXMW35C(GRx)	Polyester	Polyamide-imide	MW 35C	200[#]
JXMW36A, Q(ZY/XY)LB-x/220	JXMW36A, Q(ZY/XY)LB-x/220	Polyester-imide	Polyamide-imide	MW 36A	220
JXMW5C-x\$, QZ-x/155\$, xPEW/155\$, JXMW5C(GRx)\$, QZ/155(GRx)\$	JXMW5C-x, QZ-x/155, xPEW/155, JXMW5C(GRx), QZ/155(GRx)	Polyester	-	MW 5C	155[#]
JXMW73A-x\$, Q(ZY/XY)-x/220(L)\$, xEIAIW/220A\$, JXMW73A(GRx)\$	JXMW73A-x, Q(ZY/XY)-x/220(L), xEIAIW/220A, JXMW73A(GRx)	Polyester-imide	Polyamide-imide	MW 73A	220
JXMW73A-x\$, Q(ZY/XY)-x/220(L)\$, xPEAIW/220A\$, JXMW73A(GRx)\$	JXMW73A-x, Q(ZY/XY)-x/220(L), xPEAIW/220A, JXMW73A(GRx)	Polyester	Polyamide-imide	MW 73A	220
JXMW74C-x\$, QZY-x/200\$, xEIW/200\$, JXMW74C(GRx)\$, QZY/200(GRx)\$	JXMW74C-x, QZY-x/200, xEIW/200, JXMW74C(GRx), QZY/200(GRx)	Polyester-imide	-	MW 74C	200
JXMW75C-x\$, QA-x/130\$, xUEW/130\$, JXMW75C(GRx)\$, QA/130(GRx)\$	JXMW75C-x, QA-x/130, xUEW/130, JXMW75C(GRx), QA/130(GRx)	Polyurethane	-	MW 75C	130[#]
JXMW76A-x\$, QZ/N-x 180-A\$, xPEW N/180A\$, JXMW76A(GRx)\$, QZ/N 180-A(GRx)\$	JXMW76A-x, QZ/N-x 180-A, xPEW N/180A, JXMW76A(GRx), QZ/N 180-A(GRx)	Polyester	Polyamide	MW 76A	180
JXMW76C-x\$, QZ/N-x 180\$, xPEW N/180\$, JXMW76C(GRx)\$, QZ/N 180(GRx)\$	JXMW76C-x, QZ/N-x 180, xPEW N/180, JXMW76C(GRx), QZ/N 180(GRx)	Polyester	Polyamide	MW 76C	180
JXMW77C-x, QZ/H-x 180, xSPEW/180, JXMW77C(GRx), QZ/H 180(GRx)	JXMW77C-x, QZ/H-x 180, xSPEW/180, JXMW77C(GRx), QZ/H 180(GRx)	Polyester	-	MW 77C	180
JXMW79C-x\$, QA-x/155\$, xUEW/155\$, JXMW79C(GRx)\$, QA/155(GRx)\$	JXMW79C-x, QA-x/155, xUEW/155, JXMW79C(GRx), QA/155(GRx)	Polyurethane	-	MW 79C	155[#]
JXMW80A-x\$, QA/N-x 155-A\$, xUEW N/155A\$, JXMW80A(GRx)\$, QA/N 155-A(GRx)\$	JXMW80A-x, QA/N-x 155-A, xUEW N/155A, JXMW80A(GRx), QA/N 155-A(GRx)	Polyurethane	Polyamide	MW 80A	155[#]
JXMW80C-x\$, QA/N-x 155\$, xUEW N/155\$, JXMW80C(GRx)\$, QA/N 155(GRx)\$	JXMW80C-x, QA/N-x 155, xUEW N/155, JXMW80C(GRx), QA/N 155(GRx)	Polyurethane	Polyamide	MW 80C	155[#]
JXMW82C-x\$, QA-x/180\$, xUEW/180\$, JXMW82C(GRx)\$, QA/180(GRx)\$	JXMW82C-x, QA-x/180, xUEW/180, JXMW82C(GRx), QA/180(GRx)	Polyurethane	-	MW 82C	180

JXMW83C-x\$, QA/N-x 180\$, xUEW N/180\$, JXMW83C(GRx)\$, QA/N 180(GRx)\$	JXMW83C-x, QA/N-x 180, xUEW N/180, JXMW83C(GRx), QA/N 180(GRx)	Polyurethane	Polyamide	MW 83C	180
QZY-x/180\$, xEIW/180\$	QZY-x/180, xEIW/180	Polyester-imide	-	MW 30C	180[#]

Material Designation	Mark Dsg	Base Coat	Top Coat	Bond Coat	ANSI Type	Temp Class
EI/AIWA-x\$, Q(ZY/XY)-A-x\$	EI/AIWA-x, Q(ZY/XY)-A-x	Polyester-imide	Polyamide-imide	-	Al	240
JDMW102C-x	JDMW102C-x	Polyester-amide	Polyamide-imide	Self-bonding coat	MW 102C	180[#]
JXMW102A-x, xSBEIW/180A	JXMW102A-x, xSBEIW/180A	Polyester-amide	Polyamide-imide	self-bonding coat	MW 102A	180[#]
JXMW30A-x\$, QZ-x/180A\$, xPEW/180A\$, JXMW30A(GRx)\$, QZ/180A(GRx)\$	JXMW30A-x, QZ-x/180A, xPEW/180A, JXMW30A(GRx), QZ/180A(GRx)	Polyester	-	-	Al	180
JXMW5A-x\$, QZ-x/155A\$, xPEW/155A\$, JXMW5A(GRx)\$, QZ/155A(GRx)\$	JXMW5A-x, QZ-x/155A, xPEW/155A, JXMW5A(GRx), QZ/155A(GRx)	Polyester	-	-	Al	155[#]
JXMW74A-x\$, QZY-x/200A\$, xEIW/200A\$, JXMW74A(GRx)\$, QZY/200A(GRx)\$	JXMW74A-x, QZY-x/200A, xEIW/200A, JXMW74A(GRx), QZY/200A(GRx)	Polyester-imide	-	-	Al	200
JXMW75A-x\$, QA-x/130A\$, xUEW/130A\$, JXMW75A(GRx)\$, QA/130A(GRx)\$	JXMW75A-x, QA-x/130A, xUEW/130A, JXMW75A(GRx), QA/130A(GRx)	Polyurethane	-	-	Al	130[#]
JXMW79A-x\$, QA-x/155A\$, xUEW/155A\$, JXMW79A(GRx)\$, QA/155A(GRx)\$	JXMW79A-x, QA-x/155A, xUEW/155A, JXMW79A(GRx), QA/155A(GRx)	Polyurethane	-	-	Al	155[#]
JXMW82A-x\$, QA-x/180A\$, xUEW/180A\$, JXMW82A(GRx)\$, QA/180A(GRx)\$	JXMW82A-x, QA-x/180A, xUEW/180A, JXMW82A(GRx), QA/180A(GRx)	Polyurethane	-	-	Al	180

JXMW83A-x\$, QA/N-x 180-A\$, xUEW N/180A\$, JXMW83A(GRx)\$, QA/N 180-A(GRx)\$	JXMW83A-x, QA/N-x 180-A, xUEW N/180A, JXMW83A(GRx), QA/N 180-A(GRx)	Polyurethane	Polyamide	-	Al	180
Q(ZY/XY)-x/200(L)\$, xEIAIW/200A\$	Q(ZY/XY)-x/200(L), xEIAIW/200A	Polyester-imide	Polyamide-imide	-	Al	200[#]
Q(ZY/XY)-x/200(L)\$, xPEAIW/200A\$	Q(ZY/XY)-x/200(L), xPEAIW/200A	Polyester	Polyamide-imide	-	Al	200[#]
Q(ZY/XY)-x/200CCA	Q(ZY/XY)-x/200CCA	Polyester-imide	Polyamide-imide	-	copper clad aluminum conductor	200
Q(ZY/XY)-xB/200(L), xSBEIAIW/200A	Q(ZY/XY)-xB/200(L), xSBEIAIW/200A	Polyester-imide	Polyamide-imide	Self-bonding coat	Al	200
Q(ZY/XY)BP-x/200(L)\$	Q(ZY/XY)BP-x/200(L)\$	Polyester-imide	Polyamide-imide	-	Al	200[#]
		Polyester	Polyamide-imide	-	Al	200[#]
Q(ZY/XY)LB-x/200	Q(ZY/XY)LB-x/200	Polyester	Polyamide-imide	-	Al	200[#]
Q(ZY/XY)LJ-x/220	Q(ZY/XY)LJ-x/220	Polyester-imide	Polyamide-imide	-	Al	220
Q(ZY/XY)N-xB/200, xSBEI/AIW-200	Q(ZY/XY)N-xB/200, xSBEI/AIW-200	Polyester-imide	Polyamide-imide	Self-bonding coat	-	200
QZ-x/130\$, xPEW/130\$, QZ/130(GRx)\$	QZ-x/130, xPEW/130, QZ/130(GRx)	Polyester	-	-	-	130[#]
QZ-x/130A\$, xPEW/130A\$, QZ/130A(GRx)\$	QZ-x/130A, xPEW/130A, QZ/130A(GRx)	Polyester	-	-	Al	130[#]
QZ/N-x 130-A\$, xEIW N/130A\$, QZ/N 130-A(GRx)\$	QZ/N-x 130-A, xEIW N/130A, QZ/N 130-A(GRx)	Polyester	Polyamide	-	Al	130[#]
QZY-x/180A\$, xEIW/180A\$, QZY/180A(GRx)\$	QZY-x/180A, xEIW/180A, QZY/180A(GRx)	Polyester-imide	-	-	Al	180[#]
xEIAIW/200CCA	xEIAIW/200CCA	Polyester-imide	Polyamide-imide	-	copper clad aluminum conductor	200
xPEAIW/200CCA	xPEAIW/200CCA	Polyester-imide	Polyamide-imide	-	copper clad aluminum conductor	200

- [#] - The magnet wire may perform better than the rating reflects and may not be suitable for insulation system, varnish or end-product testing. Further consideration is necessary prior to its use in testing.
- \$ - The manufacturer 100601-278 is authorized to only produce magnet wires marked \$.
- x - May be prefixed by 0, 1, 2, 3 to indicate coating thickness.

Marking: Company name or trademark  广东精迅特种线材有限公司 ,
Guangdong JingXun Special Wire Co.,Ltd

 铜陵精迅特种漆包线有限责任公司 , material designation or marked designation on the shipping spool label or
TONGLING JINGXUN SPECIAL ENAMELLED WIRE CO LTD

smallest unit container in which the product is packaged.

Last Updated on 2024-06-29

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."